

Datacard® CP60™ Plus Card Printer



*Delivering the fastest speeds
in the Datacard portfolio,
the CP60 Plus card printer
maximizes productivity for
brilliant, one- or two-sided secure
IDs and casino/loyalty cards.*

High-impact speed and versatility

Choose the Datacard® CP60™ Plus card printer for outstanding speed and superior operational versatility. This fast printer helps maximize productivity, delivering up to 190 full-color, one-sided cards or up to 1,000 single-color, one-sided cards per hour. The CP60 Plus card printer also offers two-sided printing and many other card personalization capabilities. All of which make it ideal for printing secure IDs for corporate and education environments, as well as loyalty cards and VIP cards for casinos. It is also optimized to work with Datacard® IDCentre™ identification software and capture solutions, as part of a fully integrated system.

Smart features for multiple technologies

- Smart card, proximity card and magnetic stripe options support multi-technology photo IDs as well as cards for loyalty, retail and membership programs.
- Connectivity options include USB and built-in Ethernet for convenient network access.
- The innovative printer driver provides message prompts, color image previews and online user help from the LCD panel.
- Exclusive Advanced Image Technology™ delivers true edge-to-edge printing and sharp image quality.



DatacardGroup
SECURE ID AND CARD PERSONALIZATION SOLUTIONS

Datacard® CP60™ Plus Card Printer

Quick-change supplies switch out in seconds

100- or 200-card input hopper

Front-facing output hopper saves space



Standard LCD panel offers at-a-glance print status

Standard Ethernet and USB connectivity

The CP60 Plus card printer is an ideal choice for issuing corporate and education IDs, casino/loyalty cards and more.

Standard features

- One- or two-sided edge-to-edge printing
- Continuous-tone for full-color or black-and-white photos
- Alphanumeric text, logos and digitized signatures
- Variety of bar codes and background patterns
- Automatic printer settings and offsets, automatic ribbon identification, validation and low ribbon warning
- Full-color print speed of up to 190 cards per hour (one-sided) and up to 155 cards per hour (two-sided) and monochrome print speed of up to 1,000 cards per hour (one-sided) and up to 450 cards per hour (two-sided)
- Backlit LCD panel
- Printer pooling
- Connectivity:
 - Bi-directional USB and Ethernet 10/100 Base-T bi-directional networking
- Printer driver features user-adjustable image and color controls, stand-alone driver diagnostics, image and test card previewing, online user help and supply usage tab
- Audible and visual message prompts on printer and PC
- Automatic card feed
- Operator-replaceable printhead
- Continuous cleaning roller
- Easy access components, including quick-change ribbon cartridges
- Highly accessible card path
- 30-month standard depot printer and printhead warranty

Options

- One- or two-sided printing
- ISO magnetic stripe encoding (IAT; dual high-and low-coercivity; tracks 1, 2 and 3 for IAT)
- Smart card options include contact and contactless all-in-one reader; Contact PC USB reader; contact station; Prox by HID; and iCLASS® by HID
- Magnetic stripe and smart card field upgradeability
- 100- or 200-card input hopper
- 200-card output hopper
- Locking input hopper
- Kensington® security lock for printer
- Soft-sided carrying case
- Support for OpenCard data format
- Clear card personalization
- Input hopper empty alert

Specifications

- Dimensions: L 21.5 in. x W 7.8 in. x H 9.5 in. to H 11.9 in. (54.6 cm x 19.8 cm x 24.1 cm to 30.2 cm)
- Weight: less than 11 lbs. (5.3 kg) without supplies
- Print resolution of 300 dots per inch, 256 shades
- Electrical requirements of 100/120V, 50/60 Hz; or 220/240V, 50/60 Hz
- Accepts ISO ID-1/CR-80 size cards measuring 3.370 in. x 2.125 in. (85.6 mm x 53.98 mm); accepts glossy-surfaced PVC cards; accepts clear cards; other core materials with PVC overlaminates are optional
- Accepts card thickness from 0.009 to 0.055 in. (0.2286 mm to 1.397 mm)
- Operates in temperatures from 60° to 95° F (15° to 35° C) and non-condensing humidity from 20% to 80%
- Operating system support:
 - Microsoft® Windows Vista®, Windows® XP, Windows® 2003 Server, Windows® 2008 Server, supported on printer driver version 4.1
 - Windows® 2000 supported by printer driver version 2.1
 - Datacard® Open Platform printer driver for non-Windows platforms
- Agency approvals: UL, cUL, FCC, CE, CCC, Ctick, RoHS

Datacard® Certified Supplies featuring Intelligent Supplies Technology™

Datacard Group sales channels are your exclusive source for Datacard® Certified Supplies. Datacard® CP Plus Series card printers require the use of Datacard Certified Supplies in order to print properly.

DatacardGroup

1111 Bren Road West
Minnetonka, MN 55343-9015
+1 952 933 1223
www.datacard.com