

# Technical Specification

## Printing system

Dye sublimation re-transfer

Printing density 600dpi x 600dpi

## Printing overview

Double sided printing

Full colour 256 gradations - Dye-sublimation printing

UV printing

Text, numeric, logo's 1D, 2D Bar code

## Card personalisation speed

YMCKK Double sided printing

54 sec single side

## Printer overview

Card hopper

100 cards

Card output hopper

100 Cards

Optional card hopper

250 Cards

Card specification

0.25mm ~ 1.00mm Size: 54.0mm \* 85.6mm

## Dimensions, weight & operating environment

Dimensions

343mm \* 335mm \* 322mm (W\*H\*D) (without card stacker)

Mass approx.

Dual side 13.7kg

Temperature

15°C to 30°C Humidity: 35% to 70% (YMCK ink, No condensation)

## Operating systems and security features

Microsoft® Windows®10 32bit/64bit

Microsoft® Windows®8 (including 8.1) 32bit/64bit

Microsoft® Windows®7 (SP1) 32bit/64bit

Microsoft® Windows® Server 2012 64Bit

Microsoft® Windows® Server 2008 R2 (SP1) 64Bit

Interface USB2.0 (Hi-speed / Full Speed)

Ethernet (100BASE-TX / 10BASE-T)

Electronic locking system for input hopper, colour ribbon and INTM Film

## Software development kit

K-Series optional SDK (Contact your local sales office)

## Encoding options

Magnetic stripe encoder (K30D and K60 only)

Smart card contact/ contactless

## Warranties

36 month printer warranty

## Included in the printer

Power cord

Cleaning card

Printer driver CD

Quick install guide